


## 375 IN Slim



**P1.5                      P1.8                      P2                      P2.5                      P3**

### MODULE PARAMETERS

<b>Pixel pitch</b>	1.53mm	1.86mm	2mm	2.5 mm	3.91 mm
<b>Module size</b>	320 x 160 mm				
<b>LED type</b>	SMD1212	SMD1415	SMD1415	SMD2020	SMD2020
<b>Module resolution</b>	208x104	172*86	160*80	128*64	104*52

### CABINET SPECIFICATIONS

<b>Cabinet size</b>	640*480*45				
<b>Cabinet Materials</b>	Die-casting Aluminium				

### TECHNICAL SPECIFICATIONS

<b>Weight</b>	29 Kg/sqm				
<b>Brightness</b>	500-700 nits			600-800 nits	
<b>Viewing Angle</b>	140°V - 160°H				
<b>Gray level</b>	14 bits				
<b>Refresh Rate</b>	3.840 Mhz				
<b>Power Input</b>	220_240V				
<b>Power consumption Maximun</b>	600 W			700W	
<b>Power consumption Average</b>	120 W			150 W	
<b>Life--hours</b>	> 100,000				
<b>IP grade</b>	IP43				
<b>Operating Temperature</b>	from -20 ~40				
<b>Storage Humidity</b>	10% - 90% RH				
<b>Maintenance access</b>	Front				

### ECOACTIVE FEATURES

<b>Nox &amp; Sox Abatement</b>	50.03%				
<b>Certification of pollution abetment</b>	ISO 22197 from Fraunhofer institut				
<b>Antidust</b>	Yes				
<b>Self-cleaning</b>	Yes				
<b>Anti-bacterial</b>	Yes				

