

## 375 IN The Best



**P. 0.7                      P0.9                      P1.2                      P1.5                      P1.9                      P2.5**

MODULE PARAMETERS						
Pixel pitch	0.79	0.95	1.27	1.58	1.90	2.54
Module size	152.4 X 114.3					
LED type	Flip Chip COB					
Module resolution	192*144	160*120	128*96	96*72	80*60	60*45
CABINET SPECIFICATIONS						
Cabinet size	609.6 * 342.9 * 59,7 mm					
Cabinet Materials	Die-casting aluminum					
TECHNICAL SPECIFICATIONS						
Weight	34 Kg/sqm					
Surface finish	matte					
Brightness	600 - 1.200 nits					
Viewing Angle	179°V - 179°H					
Contrast Ratio	26,000:1					
Gray level	16					
Refresh Rate	3,840 Mhz					
Power Input	110 - 220 V					
Power consumption Maximun	480 W					
Power consumption Average	160 W					
Life--hours	> 100,000					
IP grade	IP54 Front / IP43 Back					
Shock Prook	IK 7					
Operating Temperature	from -20 ~60					
Storage Humidity	10% - 90% RH					
Maintenance access	Front or Rear					
ECOACTIVE FEATURES						
Nox & Sox Abatement	50,03%					
Certification of pollution abetment	ISO 22197 from Fraunhofer institut					
Antidust	Yes					
Self-cleaning	Yes					
Anti-bacterial	Yes					