

375 OUT DIP High brightness



P10

P10.4

P16

MODULE PARAMETERS			
Pixel pitch	10 mm	10.4 mm	15.6 mm
Module size	480*320 mm	250*250 mm	480*320 mm
LED type	DIP 346		
Module resolution	48*32	24*24	30*20
CABINET SPECIFICATIONS			
Cabinet size	960*960	500 x 1,000 mm	960*960 mm
Cabinet Resolutions	96*96	48*96	60*60
Cabinet Materials	Aluminum		
TECHNICAL SPECIFICATIONS			
Weight	32 kg/m ²	37 kg/m ²	32 kg/m ²
Brightness	12,000 nits	15,000 nits	14,000 nits
Viewing Angle	120°H - 120°V		
Grey level	16 bits		
Refresh Rate	3,840 Hz		
Power Input	AC 220 V / 50 Hz		
Power consumption Maximun	600 w/m ²	680 w/m ²	580 w/m ²
Power consumption Average	170 w/m ²	185 w/m ²	145 w/m ²
Life--hours	100,000 hours		
IP grade	IP66 Front / IP65 Back	IP 67	IP66 Front / IP65 Back
Operating Temperature	from -20 ~60		
Storage Humidity	10%~90% RH		
Maintenance access	Front / Rear		
ECOACTIVE FEATURES			
Nox & Sox Abatement	50.03%		
Certification of pollution abetment	ISO 22197 from Fraunhofer institut		
Antidust	Yes		
Self-cleaning	Yes		
Anti-bacterial	Yes		

