


375 OUT Std



P3.91

P4.81

| MODULE PARAMETERS | | |
|-------------------------------------|------------------------------------|-----------|
| Pixel pitch | P3.91 | P4.81 |
| Module size | 250 x 250 mm | |
| LED type | SMD1820 | |
| Module resolution | W64 x H64 | W52 x H52 |
| CABINET SPECIFICATIONS | | |
| Cabinet size | 500x500 / 500x1,000 mm | |
| Cabinet Resolutions | 128x128 / 128x256 | |
| Cabinet Materials | Aluminium | |
| TECHNICAL SPECIFICATIONS | | |
| Weight | 28 Kg/sqm | |
| Brightness | 5,000 nits | |
| Viewing Angle | 160°V - 160°H | |
| Gray level | 14 bits | |
| Refresh Rate | 3,840 Mhz | |
| Power Input | 110 / 220 V | |
| Power consumption Maximun | 700 W/m2 | |
| Power consumption Average | 180 W/m2 | |
| Life--hours | > 100,000 | |
| IP grade | IP65 Front / IP54 Back | |
| Operating Temperature | from -20 ~60 | |
| Storage Humidity | 10 ~90 RH | |
| Maintance access | Front / Rear | |
| ECOACTIVE FEATURES | | |
| Nox & Sox Abatement | 50.03% | |
| Certification of pollution abetment | ISO 22197 from Fraunhofer institut | |
| Antidust | Yes | |
| Self-cleaning | Yes | |
| Anti-bacterial | Yes | |