

375 OUT Transparent



	P15.6x15.6	P15.6 X 31.2	P31,2X31,2
MODULE PARAMETERS			
Pixel pitch	15.6H x 15.6V	15.6H x 31.2V	31.2H x 31.2V
Module size	1,000 x 23.8 mm		
LED type	DIP 346 - EPISTAR		
Module resolution	64 x 2		
CABINET SPECIFICATIONS			
Cabinet size	500 x 1,000	500 x 1,000	500 x 1,500
Cabinet Resolutions	32 x 64	32 x 32	16 x 48
Cabinet Materials	Aluminium		
TECHNICAL SPECIFICATIONS			
Weight	20 kg m2	16 Kg sqm	12 Kg sqm
Brightness	12,000 nits	11,000 nits	8,500 nits
Transparency Rate	24%	46%	68%
Viewing Angle	120°V - 120°H		
Refresh Rate	3.840 Mhz		
Power Input	110 - 220 V		
Power consumption Maximun	680 W	630 W	390 W
Power consumption Average	180 W	150 W	95 W
Life--hours	>100,000		
IP grade	IP67 Front / IP67 Back		
Operating Temperature	from -20 ~60		
Storage Humidity	10 ~90 RH		
Maintenance access	Front / Rear		
ECOACTIVE FEATURES			
Nox & Sox Abatement	50.03%		
Certification of pollution abetment	ISO 22197 from Fraunhofer institut		
Antidust	Yes		
Self-cleaning	Yes		
Anti-bacterial	Yes		