




IN Slim

Datasheet



	P1.25	P1.53	P1.86	P2.5
MODULE PARAMETERS				
Pixel pitch	1.25mm	1.53mm	1.86mm	2.5mm
Module size	320 x 160 mm			
LED type	SMD1010	SMD1212	SMD1515	
Module resolution	256 x 128	208 x 104	172 x 86	128 x 64
CABINET SPECIFICATIONS				
Cabinet size	640 x 480 x 50 mm			
Cabinet Materials	Die casting Aluminium			
TECHNICAL SPECIFICATIONS				
Weight per cabinet	5.5 Kg			
Brightness	400 nits	500 nits	600 nits	700 nits
Contrast Ratio	8,000:1			
Viewing Angle	160°V - 160°H			
Gray level	16 bits			
Refresh Rate	3.840 Hz			
Color temperature	7500° K			
Power Input	AC105-AC240 50-60 Hz			
Maximun Power comsuption	500 W/m2	800 W/m2		
Medium Power comsuption	150 W/m2	260 W/m2		
Life--hours	> 100,000			
IP grade	IP31			
Operating Temperature	from -10°C~45°C			
Storage Humidity	10% - 80% RH			
Maintenance access	Front			
ECOACTIVE FEATURES				
Nox & Sox Abatement	50.03%			
Certification of pollution abetment	ISO 22197 from Fraunhofer institut			
Antidust	Yes			
Self-cleaning	Yes			
Anti-bacterial	Yes			