

375 OUT Sports



	P6	P8	P10
MODULE PARAMETERS			
Pixel pitch	6 mm	8 mm	10 mm
Module size	192 x 192 mm	320 x 160 mm	
LED type	SMD 2727	SMD 3535	SMD 3535
Module resolution	32 x 32	40 x 20	32 x 16
CABINET SPECIFICATIONS			
Cabinet Dimensions (W x H)	960 x 960 mm		
Cabinet Resolution	160 x 160	120 x 120	96 x 96
Cabinet Material	Iron		
TECHNICAL SPECIFICATIONS			
Weight	49 kg/m ²		
Brightness	5,500 nits	6,500 nits	
Viewing Angle	160°H - 160°V		
Gray level	15 bits		
Refresh Rate	3,840 Hz		
Power Input	110v~240v +- 10%		
Power consumption Maximun	860 W/sqm	800 W/sqm	750 W/sqm
Power consumption Average	220 W/sqm	200 W/sqm	180 W/sqm
Life--hours	> 100,00+B20:F210 hours		
IP grade	IP65 Front / IP54 Back		
Operating Temperature	from -30°C~60°C		
Storage Humidity	10%~90% RH		
Maintenance access	front/rear		
ECOACTIVE FEATURES			
Nox & Sox Abatement	50.03%		
Certification of pollution abetment	ISO 22197 from Fraunhofer institut		
Antidust	Yes		
Self-cleaning	Yes		
Anti-bacterial	Yes		