

375 OUT Transparent



| | P15.6x15.6 | P15.6 X 31.2 | P31,2X31,2 |
|-------------------------------------|------------------------------------|---------------|---------------|
| MODULE PARAMETERS | | | |
| Pixel pitch | 15.6H x 15.6V | 15.6H x 31.2V | 31.2H x 31.2V |
| Module size | 1,000 x 23.8 mm | | |
| LED type | DIP 346 - EPISTAR | | |
| Module resolution | 64 x 2 | | |
| CABINET SPECIFICATIONS | | | |
| Cabinet size (W x H) | 500 x 1,000 | 500 x 1,000 | 500 x 1,500 |
| Cabinet Resolutions | 32 x 64 | 32 x 32 | 16 x 48 |
| Cabinet Materials | Aluminum | | |
| TECHNICAL SPECIFICATIONS | | | |
| Weight | 20 kg m2 | 16 Kg sqm | 12 Kg sqm |
| Brightness | 12,000 nits | 11,000 nits | 8,500 nits |
| Transparency Rate | 24% | 46% | 68% |
| Viewing Angle | 120°V - 120°H | | |
| Refresh Rate | 3.840 Mhz | | |
| Power Input | 110 - 220 V | | |
| Power consumption Maximun | 680 W | 630 W | 390 W |
| Power consumption Average | 180 W | 150 W | 95 W |
| Life--hours | >100,000 | | |
| IP grade | IP67 Front / IP67 Back | | |
| Operating Temperature | from -20 ~60 | | |
| Storage Humidity | 10 ~90 RH | | |
| Maintenance access | Front / Rear | | |
| ECOACTIVE FEATURES | | | |
| Nox & Sox Abatement | 50.03% | | |
| Certification of pollution abetment | ISO 22197 from Fraunhofer institut | | |
| Antidust | Yes | | |
| Self-cleaning | Yes | | |
| Anti-bacterial | Yes | | |