

375 OUT +



P2.9 P3.9 P4.8 P5.7 P6.6 P8 P10

MODULE PARAMETERS							
Pixel pitch	2.9	3.9	4.8	5.7	6.6	8	10
Module size	500x250			160x160			
LED type	SMD1921	SMD1921	SMD1921	SMD2727	SMD2727	SMD3535	SMD3535
Module resolution	168x84	128x64	104x52	28x28	24x24	20x20	16x16
CABINET SPECIFICATIONS							
Cabinet size (W x H)	500x500	500x500/ 500x1,000	500x500/ 500x1,000	960x960			
Cabinet Materials	Aluminum						
TECHNICAL SPECIFICATIONS							
Weight	34 Kg/sqm						
Brightness	4,000 nits	5,000 nits		6,000 nits		7,000 nits	
Viewing Angle	160°V - 160°H						
Gray level	16						
Refresh Rate	3,840 Mhz						
Power Input	110 - 220 V						
Power consumption Maximun	650			520			
Power consumption Average	170			130			
Life--hours	> 100,000						
IP grade	IP65						
Operating Temperature	from -20 ~60						
Storage Humidity	10% - 90% RH						
Maintenance access	Front / Rear						
ECOACTIVE FEATURES							
Nox & Sox Abatement	50.03%						
Certification of pollution abetment	ISO 22197 from Fraunhofer institut						
Antidust	Yes						
Self-cleaning	Yes						
Anti-bacterial	Yes						