



375 IN Std



P2.5

P2.9

P3.9

MODULE PARAMETERS			
Pixel pitch	2.5 mm	2.98 mm	3.91 mm
Module size	250 x 250 mm		
LED type	SMD2121	SMD 2020	
Module resolution	100 x 100	84 x 84	64 x 64
CABINET SPECIFICATIONS			
Cabinet size	500 x 500 x70 mm   500 x 1,000 x 70mm		
Cabinet Materials	Aluminium		
TECHNICAL SPECIFICATIONS			
Weight	29 Kg/sqm		
Brightness	800 - 1,200 nits		
Contrast	5,000:1		
Viewing Angle	160°V - 160°H		
Gray level	16		
Refresh Rate	3.840 Mhz		
Power Input	110 - 220 V		
Power consumption Maximun	750 W	720 W	680 W
Power consumption Average	180 W	160 W	120 W
Life--hours	> 100,000		
IP grade	IP43		
Operating Temperature	from -20°C~60°C		
Storage Humidity	10% - 90% RH		
Maintenance access	Front		
ECOACTIVE FEATURES			
Nox & Sox Abatement	50.03%		
Certification of pollution abetment	ISO 22197 from Fraunhofer institut		
Antidust	Yes		
Self-cleaning	Yes		
Anti-bacterial	Yes		

