


375 IN Slim



P1.5 P1.8 P2 P2.5 P3

MODULE PARAMETERS

Pixel pitch	1.53mm	1.86mm	2mm	2.5 mm	3.076 mm
Module size	320 x 160 mm				
LED type	SMD1212	SMD1415	SMD1415	SMD2020	SMD2020
Module resolution	208x104	172*86	160*80	128*64	104*52

CABINET SPECIFICATIONS

Cabinet size	640*480*45				
Cabinet Materials	Die-casting Aluminium				

TECHNICAL SPECIFICATIONS

Weight	29 Kg/sqm				
Brightness	500-700 nits			600-800 nits	
Viewing Angle	140°V - 160°H				
Gray level	14 bits				
Refresh Rate	3.840 Mhz				
Power Input	220_240V				
Power consumption Maximun	600 W			700W	
Power consumption Average	120 W			150 W	
Life--hours	> 100,000				
IP grade	IP43				
Operating Temperature	from -20 ~40				
Storage Humidity	10% - 90% RH				
Maintenance access	Front				

ECOACTIVE FEATURES

Nox & Sox Abatement	50.03%				
Certification of pollution abetment	ISO 22197 from Fraunhofer institut				
Antidust	Yes				
Self-cleaning	Yes				
Anti-bacterial	Yes				

