




375 IN Transparent



	P2.6	P3.4	P2.6-6.9	P3.9-7.8	P7.8
MODULE PARAMETERS					
Pixel pitch	2.6H - 2.6V mm	3.4H - 3.4V mm	2.6H - 6.9V mm	3.9H - 7.8V mm	7.8H - 7.8V mm
Module size	500 x 62.5 mm	500 x 83.28 mm	500 x 250 mm	50 x 500mm	50 x 500mm
LED type	SMD 1415	SMD 1415	SMD 1820	SMD 1921	SMD 1921
Module resolution	192 x 24	144 x 24	192 x 36	128 x 32	64 x 32
CABINET SPECIFICATIONS					
Cabinet size	1,000 x 500 mm	1,000 x 1,000 mm	1,000 x 500 mm	1,000 x 500 mm	1,000 x 500 mm
Cabinet Resolutions	384 x 192	288 x 288	384 x 72	240 x 64	128 x 64
Cabinet Materials	aluminum				
TECHNICAL SPECIFICATIONS					
Weight	11 kg/m ²	11 kg/m ²	24 kg/m ²	24 kg/m ²	24 kg/m ²
Brightness	5,000 nits	5,000 nits	3,500 nits	5,000 nits	5,000 nits
Contrast Ratio	50%	65%	60%	70%	75%
Viewing Angle	160° H - 160° V				
Gray level	14 bits				
Refresh Rate	1920-3,840 Hz				
Power Input	AC 100V ~ 240V				
Power consumption Maximun	800 w/m ²	800 w/m ²	800 w/m ²	250 w/m ²	200 w/m ²
Power consumption Average	240 w /m ²	240 w /m ²	250 w /m ²	96 w /m ²	96 w /m ²
Life--hours	> 100,000 hours				
IP grade	IP30	IP30	IP20	IP20	IP20
Operating Temperature	from -20°C~60°C				
Storage Humidity	35%~90%RH				
Maintance access	front/rear				
ECOACTIVE FEATURES					
Nox & Sox Abatement	50.03%				
Certification of pollution abetment	ISO 22197 from Fraunhofer institut				
Antidust	Yes				
Self-cleaning	Yes				
Anti-bacterial	Yes				

