

375 IN All In One


P1.25 / 108"
P1.56 / 135"
P1.87 / 162"

| MODULE PARAMETERS | | | |
|-------------------------------------|--|---------|---------|
| Pixel pitch | 1.25 mm | 1.56 mm | 1.87mm |
| Diagonal (inches) | 108" | 135" | 162" |
| Module size | 300mm x 168,75mm | | |
| LED type | SMD1010 | | SMD1515 |
| Screen resolution | 1,920 x 1,080 | | |
| CABINET SPECIFICATIONS | | | |
| Cabinet size | 600mm x 337,5mm | | |
| Cabinet Materials | Die casting Aluminium | | |
| TECHNICAL SPECIFICATIONS | | | |
| Screen Weight (wall hanging) | 76 kg | 115 kg | 162 kg |
| Screen Weight (bracket) | 128 kg | 168 kg | 238 kg |
| Brightness | 1000 nits | | |
| Contrast Ratio | 10,000:1 | | |
| Viewing Angle | 140°V - 160°H | | |
| Gray level | 16 bit | | |
| Refresh Rate | 3.840 Hz | | |
| Power Input | AC220~AC240 | | |
| Maximun Power consumption | 600 W/m2 | | |
| Average Power consumption | 200 W/m2 | | |
| Life--hours | > 100,000 | | |
| Operating Temperature | from -10°C~40°C | | |
| Storage Humidity | 10% - 80% RH | | |
| Maintenance access | Front | | |
| Input/Output | Audio in (S/PDIF) / HDMI Input / 3 USB port / RJ45(Ethernet) | | |
| ECOACTIVE FEATURES | | | |
| Nox & Sox Abatement | 50.03% | | |
| Certification of pollution abetment | ISO 22197 from Fraunhofer institut | | |
| Antidust | Yes | | |
| Self-cleaning | Yes | | |
| Anti-bacterial | Yes | | |