

## IN All In One GOB


**P1.25 / 108"**
**P1.56 / 135"**
**P1.87 / 162"**

<b>MODULE PARAMETERS</b>			
Pixel pitch	1.25 mm	1.56 mm	1.87mm
Diagonal (inches)	108"	135"	162"
Module size	300mm x 168,75mm		
LED type	SMD1010		SMD1515
Screen resolution	1,920 x 1,080		
<b>CABINET SPECIFICATIONS</b>			
Cabinet size	600mm x 337,5mm		
Cabinet Materials	Die casting Aluminium		
<b>TECHNICAL SPECIFICATIONS</b>			
Screen Weight (wall hanging)	76 kg	115 kg	162 kg
Screen Weight (bracket)	128 kg	168 kg	238 kg
Brightness	1000 nits		
Contrast Ratio	10,000:1		
Viewing Angle	140°V - 160°H		
Gray level	16 bits		
Refresh Rate	3.840 Hz		
Power Input	AC220-AC240		
Maximun Power consumption	600 W/m <sup>2</sup>		
Average Power consumption	200 W/m <sup>2</sup>		
Life--hours	> 100,000		
Operating Temperature	from -10°C~40°C		
Storage Humidity	10% - 80% RH		
Maintenance access	Front		
Input/Output	Audio in (S/PDIF) / HDMI Input / 3 USB port / RJ45(Ethernet)		
<b>ECOACTIVE FEATURES</b>			
Nox & Sox Abatement	50.03%		
Certification of pollution abetment	ISO 22197 from Fraunhofer institut		
Antidust	Yes		
Self-cleaning	Yes		
Anti-bacterial	Yes		