

## 375 IN Multi-size



	<b>P1.56</b>	<b>P1.95</b>	<b>P2.6</b>	<b>P3.9</b>
<b>MODULE PARAMETERS</b>				
<b>Pixel pitch</b>	1.56 mm	1.95 mm	2.6 mm	3.9mm
<b>Module size</b>	250 x 250 mm			
<b>Module resolution</b>	160 X 160	128 X 128	96 x 96	64 x 64
<b>CABINET SPECIFICATIONS</b>				
<b>Cabinet size</b>	500 x 250   250 x 500   500 x 500   500 x 1000mm			
<b>Cabinet thickness</b>	39,6mm			
<b>Cabinet Materials</b>	Die casting Aluminium			
<b>TECHNICAL SPECIFICATIONS</b>				
<b>Weight per cabinet</b>	3.2Kg   5.6Kg   11kg			
<b>Brightness</b>	600 - 800 nits	800 - 1000 nits	1000 - 1200 nits   1000 - 4000 nits	
<b>Contrast Ratio</b>	6,000:1			
<b>Viewing Angle</b>	179°V - 179°H			
<b>Gray level</b>	14 -16 bits			
<b>Refresh Rate</b>	3.840 Hz			
<b>Power Input</b>	AC200~AC240			
<b>Maximun Power consupction</b>	224 W/m2	340 W/m2	480 W/m2	500 W/m2
<b>Average Power Consumption</b>	77 W/m2	120 W/m2	160 W/m2	170 W/m2
<b>Life--hours</b>	> 100,000			
<b>IP grade</b>	IP20 Front / IP30 Rear			
<b>Operating Temperature</b>	from -20°C~60°C			
<b>Storage Humidity</b>	10% - 90% RH			
<b>Maintenance access</b>	Front/Rear			
<b>ECOACTIVE FEATURES</b>				
<b>Nox &amp; Sox Abatement</b>	50.03%			
<b>Certification of pollution abetment</b>	ISO 22197 from Fraunhofer institut			
<b>Antidust</b>	Yes			
<b>Self-cleaning</b>	Yes			
<b>Anti-bacterial</b>	Yes			