

OUT ALU 1000



	P6.25	P7.81	P10.4
Module Parameters			
Pixel pitch	6.25 mm	7.8125 mm	10.417mm
Module size	500mm (W) x 250 mm (H)		
Module resolution	80 X 40 dots	64 x 32 dots	48 x 24 dots
Cabinet Specifications			
Cabinet size	1000 x 500 1000 x 1000 1500 x 1000mm		
Cabinet Materials	Aluminium profile		
Technical Specifications			
Weight cabinet	16 kg	29.5 kg	43 kg
Brightness	6500 or 9000 nits 6500 or 9500 nits 6500 or 10000 nits		
Contrast Ratio	6,000:1		
Viewing Angle	110°V - 110°H		
Gray level	16 bits		
Refresh Rate	3.840 Hz		
Power Input	AC110~AC220 V - 50 Hz / 60 Hz		
Maximun Power consupption	580 W/m2	600 W/m2	
Average Power Consumption	165 W/m2	170 W/m2	
Life--hours	> 100,000		
IP grade	IP66		
Operating Temperature	-20°C ~ 50°C		
Operating Humidity	10% ~ 90% RH		
Maintenance access	Front/Rear		
ECOACTIVE FEATURES			
Nox & Sox Abatement	50.03%		
Certification of pollution abetment	ISO 22197 from Fraunhofer institut		
Antidust	Yes		
Self-cleaning	Yes		
Anti-bacterial	Yes		