

375 OUT Totem



	One Side	Double Side	One Side	Double Side
MODULE PARAMETERS				
Pixel pitch	2.56 mm		3.125 mm	
Module size	200 x 200 mm		200 x 200 mm	
LED type	SMD 1516		SMD 1921	
Module resolution	78 x 78		64 x 64	
DISPLAY SPECIFICATIONS				
Totem Dimensions (W x H x D)	1,050 x 2,350 x 150 mm	1,100 x 2,400 x 200 mm	1,050 x 2,350 x 150 mm	1,100 x 2,400 x 200 mm
Screen Dimensions (W x H x D)	1,000 x 1,800 mm			
Physical Resolution	390 x 702	390 x 703	320 x 576	320 x 576P/side
Material	Aluminium cabinet / Iron structure & base			
TECHNICAL SPECIFICATIONS				
	One Side		Double Side	
Weight	180 kg		320 kg	
Brightness	7,000 nits			
Viewing Angle	160° H / 160° V			
Gray level	16 bits			
Refresh Rate	3,840 Hz			
Power Input	AC 220V / 50 HZ			
Power consumption Maximun	1,260 W/ side		1378 W/ side	
Power consumption Average	230 W/ side		250 W/ Side	
Life--hours	100,000 hours			
IP grade	IP65			
Operating Temperature	from -20 ~65			
Storage Humidity	10%~90% RH			
Maintenance access	Rear			
ECOACTIVE FEATURES				
Nox & Sox Abatement	50.03%			
Certification of pollution abetment	ISO 22197 from Fraunhofer institut			
Antidust	Yes			
Self-cleaning	Yes			
Anti-bacterial	Yes			