

OUT ALU1000



P6.25

P7.81

P10.4

MODULE PARAMETERS			
Pixel pitch	6.25 mm	7.8125 mm	10.417mm
Module size	500mm (W) x 250 mm (H)		
Module resolution	80 X 40 dots	64 x 32 dots	48 x 24 dots
CABINET SPECIFICATIONS			
Cabinet size	1000 x 500 1000 x 1000 1500 x 1000mm		
Cabinet Materials	Aluminium profile		
TECHNICAL SPECIFICATIONS			
Weight	29.5 kg/sqm	29.5 kg/sqm	29.5 kg/sqm
Brightness	6500 or 9000 nits 6500 or 9500 nits 6500 or 10000 nits		
Contrast Ratio	6,000:1		
Viewing Angle	110°V - 110°H		
Gray level	16 bits		
Refresh Rate	3.840 Hz		
Power Input	AC110~AC220 V - 50 Hz / 60 Hz		
Maximun Power comsuption	580 W/m2	600 W/m2	
Average Power Consumption	165 W/m2	170 W/m2	
Life--hours	> 100,000		
IP grade	IP66		
Operating Temperature	-20°C ~ 50°C		
Operating Humidity	10% ~ 90% RH		
Maintenance access	Front/Rear		
ECOACTIVE FEATURES			
Nox & Sox Abatement	50.03%		
Certification of pollution abetment	ISO 22197 from Fraunhofer institut		
Antidust	Yes		
Self-cleaning	Yes		
Anti-bacterial	Yes		