



# IN-Multi-size front

## DATA SHEET

**P1.5**

**P1.9**

**P2.5**

**P2.6**

**P3.9**

MODULE PARAMETERS					
Pixel pitch	1.56 mm	1.9 mm	2.5 mm	2.6mm	3.9mm
Module size	250 X 250 mm				
LED type	SMD1212	SMD1515	SMD2020		
Module resolution	160x160	128x128	100x100	96x96	64x64

### CABINET SPECIFICATIONS

Cabinet size	250x250   500x250   750x250   1000x250  500x500  1000x500 mm
--------------	--

Cabinet Materials	Die casting Aluminium
-------------------	-----------------------

### TECHNICAL SPECIFICATIONS

Weight per cabinet	1.192kg   2.5kg   4kg   5.5kg   5.6kg   10.7kg				
Brightness	700 nits	1.000 nits			
Contrast Ratio	6,000:1				
Viewing Angle	160° V - 160° H				
Gray level	14 bits				
Refresh Rate	3840 Hz				
Power Input	AC100 ~ AC240 / 50~60 Hz				
Maximun Power comsuption	224 W/m2	340 W/m2	480 W/m2	500 W/m2	
Average Power comsuption	77 W/m2	120 W/m2	160 W/m2	170 W/m2	
Life--hours	> 100,000				
IP grade	IP30				
Operating Temperature	from -20°C~60°C				
Storage Humidity	10% - 90% RH				
Maintenance access	Front				

### ECOACTIVE FEATURES

Nox & Sox Abatement	50.03%				
Certification of pollution abetment	ISO 22197 from Fraunhofer institut				
Antidust	Yes				
Self-cleaning	Yes				
Anti-bacterial	Yes				