



IN-Multi-size

DATA SHEET

P1.56

P1.95

P2.6

P3.9

| MODULE PARAMETERS | | | | |
|-------------------------------------|--|-----------------|-------------------------------------|----------|
| Pixel pitch | 1.56 mm | 1.95 mm | 2.6 mm | 3.9mm |
| Module size | 250 x 250 mm | | | |
| Module resolution | 160 X 160 | 128 X 128 | 96 x 96 | 64 x 64 |
| CABINET SPECIFICATIONS | | | | |
| Cabinet size | 500 x 250 250 x 500 500 x 500 500 x 1000mm | | | |
| Cabinet thickness | 39,6mm | | | |
| Cabinet Materials | Die casting Aluminium | | | |
| TECHNICAL SPECIFICATIONS | | | | |
| Weight per cabinet | 3.2Kg 5.6Kg 11kg | | | |
| Brightness | 600 - 800 nits | 800 - 1000 nits | 1000 - 1200 nits 1000 - 4000 nits | |
| Contrast Ratio | 6,000:1 | | | |
| Viewing Angle | 160°V - 160°H | | | |
| Gray level | 14 -16 bits | | | |
| Refresh Rate | 3.840 Hz | | | |
| Power Input | AC200~AC240 | | | |
| Maximun Power consuption | 224 W/m2 | 340 W/m2 | 480 W/m2 | 500 W/m2 |
| Average Power Consumption | 77 W/m2 | 120 W/m2 | 160 W/m2 | 170 W/m2 |
| Life--hours | > 100,000 | | | |
| IP grade | IP20 Front / IP30 Rear | | | |
| Operating Temperature | from -20°C~60°C | | | |
| Storage Humidity | 10% - 90% RH | | | |
| Maintenance access | Front/Rear | | | |
| ECOACTIVE FEATURES | | | | |
| Nox & Sox Abatement | 50.03% | | | |
| Certification of pollution abetment | ISO 22197 from Fraunhofer institut | | | |
| Antidust | Yes | | | |
| Self-cleaning | Yes | | | |
| Anti-bacterial | Yes | | | |