



# OUT + DATA SHEET

	P1.95	P2.6	P2.9	P3.91	P4.81
<b>MODULE PARAMETERS</b>					
Pixel pitch	1.95 mm	2.604 mm	2.97 mm	3.91 mm	4.81 mm
Module size	250 x 250 x 18 mm				
LED type	SMD1415 GOB	SMD 1415		SMD 1921	
Module resolution	128 X 128	96 x 96	84 x 84	64 x 64	52 x 52
<b>CABINET SPECIFICATIONS</b>					
Cabinet size	500 x 500   500 x 750   500 x 1000 mm				
Cabinet Materials	Die casting Aluminium				
<b>TECHNICAL SPECIFICATIONS</b>					
Weight per cabinet	8,5 Kg (500x500mm)   12 Kg (500x750 mm)   15,5 Kg (500x1000mm)				
Brightness	≥4500 nits			≥5500 nits	
Contrast Ratio	6,000:1				
Viewing Angle	140° V - 120° H				
Gray level	16 bits				
Refresh Rate	3.840 Hz				
Power Input	AC200~AC240				
Maximun Power consupction	500 W/m2				
Life--hours	> 100,000				
IP grade	IP66 Front and Rear				
Operating Temperature	from -20°C~60°C				
Storage Humidity	10% - 90% RH				
Maintenance access	Front/Rear				
<b>ECOACTIVE FEATURES</b>					
Nox & Sox Abatement	50.03%				
Certification of pollution abetment	ISO 22197 from Fraunhofer institut				
Antidust	Yes				
Self-cleaning	Yes				
Anti-bacterial	Yes				