



# 375 IN Double

**P1.95****P2.5****P2.9****P3.9**

MODULE PARAMETERS				
Pixel pitch	1.95 mm	2.5 mm	2.98 mm	3.91 mm
Module size	250 x 250 mm			
LED type	SMD1515			SMD 2020
Module resolution	128 X 128	100 x 100	84 x 84	64 x 64
CABINET SPECIFICATIONS				
Cabinet size	1,000 x 250 x 53 mm   750 x 250 x 53 mm   500 x 250 x 53 mm			
Cabinet Materials	Aluminium			
TECHNICAL SPECIFICATIONS				
Weight	31.2 Kg/sqm			
Brightness	800 nits		800 -1,000 nits	1,000-1,200 nits
Contrast Ratio	5,000:1			
Viewing Angle	160°V - 160°H			
Gray level	14 / 16 Optical			
Refresh Rate	3,840 Hz			
Power Input	AC100-240V			
Power consumption Maximun	800 W/m2			
Power consumption Average	100-250 W/m2			
Life--hours	> 100,000 Hrs			
IP grade	IP43			
Operating Temperature	from -20°C~60°C			
Storage Humidity	10% - 90% RH			
Maintenance access	Front			
ECOACTIVE FEATURES				
Nox & Sox Abatement	50.03%			
Certification of pollution	ISO 22197 from Fraunhofer institut			
Antidust	Yes			
Self-cleaning	Yes			
Anti-bacterial	Yes			

