



OUT ALU 1000

Datasheet



	P6.25	P7.81	P10.4
MODULE PARAMETERS			
Pixel pitch	6.25mm	7.8125mm	10.417mm
Module size (W x H)	500 x 250 mm		
Module resolution	80 X 40 dots	64 X 32 dots	48 X 24 dots
CABINET SPECIFICATIONS			
Cabinet size	1000 x 500 1000 x 1000 1500 x 1000mm		
Cabinet Materials	Aluminium profile		
TECHNICAL SPECIFICATIONS			
Weight	29.5 kg/sqm		
Brightness	6500 or 9000 nits	6500 or 9500 nits	6500 or 10000 nits
Contrast Ratio	6,000:1		
Viewing Angle	110°V - 110°H		
Gray level	16 bits		
Refresh Rate	3.840 Hz		
Color temperature	7500° K		
Power Input	AC105-AC220 50-60 Hz		
Maximun Power consuption	580 W/m2	600 W/m2	
Medium Power consuption	165 W/m2	170 W/m2	
Life--hours	> 100,000		
IP grade	IP66		
Operating Temperature	from -20°C-50°C		
Storage Humidity	10% - 90% RH		
Maintenance access	Front/Rear		
ECOACTIVE FEATURES			
Nox & Sox Abatement	50.03%		
Certification of pollution abetment	ISO 22197 from Fraunhofer institut		
Antidust	Yes		
Self-cleaning	Yes		
Anti-bacterial	Yes		