



	P0.78	P0.93	P1.25	P1.56
MODULE PARAMETERS				
Pixel pitch	0.78 mm	0.93 mm	1.25 mm	1.56 mm
Module size	150 x 112.5 mm			
LED type	Flip Chip COB			
Module resolution	192 x 144	160 x 120	120 x 90	96 x 72
CABINET SPECIFICATIONS				
Cabinet size	600 x 337.5 x 44.5 mm			
Cabinet resolution	768 x 432	640 x 360	480 x 270	384 x 216
Cabinet Materials	Die casting Aluminium			
TECHNICAL SPECIFICATIONS				
Weight per cabinet	30 kg / sqm			
Surface finish	Matte			
Brightness	600 – 1.200 nits			
Contrast Ratio	26,000:1			
Viewing Angle	179°V – 179°H			
Gray level	16 bits			
Refresh Rate	3.840 Hz			
Power Input	AC110 ~AC220			
Maximun Power comsuption	480 W/m2			
Medium Power comsuption	160 W/m2			
Life hours	> 100,000			
IP grade	IP54 Front / IP43 back			
Shock Proof	IK 7			
Operating Temperature	from -20°C~60°C			
Storage Humidity	10% – 90% RH			
Maintenance access	Front			
ECOACTIVE FEATURES				
Nox & Sox Abatement	50.03%			
Certification of pollution abetment	ISO 22197 from Fraunhofer institut			
Antidust	Yes			
Self-cleaning	Yes			
Anti-bacterial	Yes			