



	One Side P2.56	Double Side P2.56	One Side P3.125	Double Side P3.125
MODULE PARAMETERS				
Pixel pitch	2.56 mm		3.125 mm	
Module size (W x H)	200 x 200 mm			
LED type	SMD 1516		SMD 1921	
Module resolution	78 x 78		64 X 64	
CABINET SPECIFICATIONS				
Totem Dimensions (W x H x D)	1.050 x 2.350 x 150 mm	1.100 x 2.400 x 200 mm	1.050 x 2.350 x 150 mm	1.100 x 2.400 x 200 mm
Screen Dimensions (W x H x D)	1.000 x 1.800 mm			
Physical Resolution	390 x 702	390 x 703	320 x 576	320 x 576P/side
Material	Aluminium cabinet / Iron structure & base			
TECHNICAL SPECIFICATIONS				
	One Side		Double Side	
Weight	180 kg		320 kg	
Brightness	7,000 nits			
Viewing Angle	160° H / 160° V			
Gray level	16 bits			
Refresh Rate	3.840 Hz			
Power Input	AC 220V / 50 Hz			
Maximun Power comsuption	1.260 W/ side		1.378 W/ side	
Power comsuption average	230 W/m2		250 W/m2	
Life hours	> 100,000			
IP grade	IP65			
Operating Temperature	from -20°C~50°C			
Storage Humidity	10% – 90% RH			
Maintenance access	Front/Rear			
ECOACTIVE FEATURES				
Nox & Sox Abatement	50.03%			
Certification of pollution abetment	CEN/TS 16980-1 / ISO 22197-1			
Antidust	Yes			
Self-cleaning	Yes			
Anti-bacterial	Yes			