



OUT EXTREME

Datasheet



	P9.525	P6.35	P3.81	P3.175
MODULE PARAMETERS				
Pixel pitch	9.525 mm	6.35 mm	3.81 mm	3.175 mm
Module size (W x H)	609.6 x 304.8 mm			
LED Type	SMD2727		SMD1921	SMD1415
Cabinet resolution	64 x 128 px	96 x 192 px	160 x 320 px	192 x 384 px
CABINET SPECIFICATIONS				
Cabinet size	1,219.02 x 609.6 mm (4ft x 2 ft)			
Cabinet Materials	Aluminium			
TECHNICAL SPECIFICATIONS				
Weight	30 kg/sqm			
Brightness	6000 nits – 8000 nits		5500 nits – 7500 nits	
Contrast Ratio	6,000:1			
Viewing Angle	120°V – 140°H			
Gray level	16 bits			
Refresh Rate	3.840 Hz			
Power Input	AC110-AC220 50-60 Hz			
Maximun Power comsuption	670-905 W/m2		550-745 W/m2	
Average Power comsuption	215-275 W/m2		180-240 W/m2	
Life hours	> 100,000			
IP grade	IP67 – IK10			
Operating Temperature	from -30°C-60°C			
Storage Humidity	10% – 90% RH			
Maintenance access	Full Front & full Rear			
ECOACTIVE FEATURES				
Nox & Sox Abatement	50.03%			
Certification of pollution abetment	CEN/TS 16980-1 / ISO 22197-1			
Antidust	Yes			
Self-cleaning	Yes			
Anti-bacterial	Yes			