



# IN HD Ultra Slim

Datasheet



|                                     | P0.9                         | P1.2      | P1.5      | P1.9     |
|-------------------------------------|------------------------------|-----------|-----------|----------|
| <b>MODULE PARAMETERS</b>            |                              |           |           |          |
| Pixel pitch                         | 0.93 mm                      | 1.25 mm   | 1.56 mm   | 1.875 mm |
| Module size                         | 300 x 168.75 mm              |           |           |          |
| LED type                            | SMD0808                      | SMD1010   |           | SMD1515  |
| Module resolution                   | 320 x 180                    | 240 x 135 | 192 x 108 | 160 x 90 |
| <b>CABINET SPECIFICATIONS</b>       |                              |           |           |          |
| Cabinet size                        | 600 x 337.5 x 22.5 mm        |           |           |          |
| Cabinet Materials                   | Die casting Aluminium        |           |           |          |
| <b>TECHNICAL SPECIFICATIONS</b>     |                              |           |           |          |
| Weight per cabinet                  | 4 Kg                         |           |           |          |
| Brightness                          | 1,000 nits                   |           |           |          |
| Contrast Ratio                      | 10,000:1                     |           |           |          |
| Viewing Angle                       | 160°V - 160°H                |           |           |          |
| Gray level                          | 16 bits                      |           |           |          |
| Refresh Rate                        | 3.840 Hz                     |           |           |          |
| Color temperature                   | 7500° K                      |           |           |          |
| Power Input                         | AC100~AC240 50~60 Hz         |           |           |          |
| Maximun Power comsuption            | 600 W/m2                     |           |           |          |
| Medium Power comsuption             | 180 W/m2                     |           |           |          |
| Life hours                          | > 100,000                    |           |           |          |
| IP grade                            | IP31                         |           |           |          |
| Operating Temperature               | from -10°C~40°C              |           |           |          |
| Storage Humidity                    | 10% - 80% RH                 |           |           |          |
| Maintenance access                  | Front                        |           |           |          |
| <b>ECOACTIVE FEATURES</b>           |                              |           |           |          |
| Nox & Sox Abatement                 | 50.03%                       |           |           |          |
| Certification of pollution abetment | CEN/TS 16980-1 / ISO 22197-1 |           |           |          |
| Antidust                            | Yes                          |           |           |          |
| Self-cleaning                       | Yes                          |           |           |          |
| Anti-bacterial                      | Yes                          |           |           |          |