




IN Transparent

Datasheet



	P2.8 - 5.6	P3.4	P2.6 - 6.9	P3.9 - 7.8	P7.8
MODULE PARAMETERS					
Pixel pitch	2.8H - 5.6V mm	3.4H - 3.4V mm	2.6H - 6.9V mm	3.9H - 7.8V mm	7.8H - 7.8V mm
Module size	500 x 250 mm	500 x 83.28 mm	500 x 250 mm	500 x 125 mm	500 x 125 mm
LED type	SMD 1820	SMD 1415	SMD 1820	SMD 1921	SMD 1921
Module resolution	176 x 22	144 x 24	192 x 36	126 x 16	64 x 16
CABINET SPECIFICATIONS					
Cabinet size	1,000 x 1,000 mm		1,000 x 500 mm		
Cabinet Resolutions	352 x 176	288 x 288	384 x 72	252 x 64	128 x 64
Cabinet Materials	Die casting Aluminium				
TECHNICAL SPECIFICATIONS					
Weight per cabinet	11 kg/m ²		12 kg/m ²		
Brightness	5000 nits		3500 nits	5000 nits	
Contrast Ratio	60%	65%	60%	70%	75%
Viewing Angle	160°V - 160°H				
Gray level	14 bits				
Refresh Rate	3.840 Hz				
Power Input	AC 100V ~ AC 240V / 50-60 Hz				
Maximum Power consumption	800 W/m ²			250 W/m ²	200 W/m ²
Medium Power consumption	240 W/m ²		250 W/m ²	96 W/m ²	
Life hours	> 100,000				
IP grade	IP30		IP20		
Operating Temperature	from -20°C~60°C				
Storage Humidity	35%-90%RH				
Maintenance access	Front / Rear				
ECOACTIVE FEATURES					
Nox & Sox Abatement	50.03%				
Certification of pollution abatement	CEN/TS 16980-1 / ISO 22197-1				
Antidust	Yes				
Self-cleaning	Yes				
Anti-bacterial	Yes				