



OUT ALU 1000

Datasheet



	P3.91	P4.81	P6.25	P7.81	P10.4
MODULE PARAMETERS					
Pixel pitch	3.906 mm	4.807 mm	6.25 mm	7.8125 mm	10.417 mm
Module size (W x H)	500 x 250 mm				
Module resolution	128 x 64 dots	104 x 52 dots	80 X 40 dots	64 X 32 dots	48 X 24 dots
CABINET SPECIFICATIONS					
Cabinet size	1000 x 500 1000 x 750 1000 x 1000 1500 x 1000 mm				
Cabinet Materials	Aluminium profile				
TECHNICAL SPECIFICATIONS					
Weight	29.5 kg/sqm				
Brightness	6500 or (9000 nits HB)	6500 or (9500 nits HB)	7000 or (9500 nits HB)	7500 or (10500 nits HB)	
Contrast Ratio	8,000:1				
Viewing Angle	160°V - 160°H				
Gray level	16 bits				
Refresh Rate	3.840 Hz				
Power Input	AC110-AC220 50-60 Hz				
Maximum Power consumption (Standard Brightness)	630 W/m ²	520 W/m ²	650 W/m ²		
Medium Power consumption	180 W/m ²	156 W/m ²	220 W/m ²		
Life hours	> 100,000				
IP grade	IP66				
Operating Temperature	from -20°C-50°C				
Storage Humidity	10% - 90% RH				
Maintenance access	Front/Rear				
ECOACTIVE FEATURES					
Nox & Sox Abatement	50.03%				
Certification of pollution abatement	CEN/TS 16980-1 / ISO 22197-1				
Antidust	Yes				
Self-cleaning	Yes				
Anti-bacterial	Yes				