



IN Double

Datasheet



	P1.95	P2.5	P2.9	P3.9
MODULE PARAMETERS				
Pixel pitch	1.95mm	2.5mm	2.98mm	3.91 mm
Module size	250 x 250 mm			
LED Type	SMD1515			SMD2020
Module resolution	128x128	100x100	84x84	64 x 64
CABINET SPECIFICATIONS				
Cabinet size	1000 x 250 mm 750 x 250 mm 500 x 250 mm			
Cabinet thickness	53 mm			
Cabinet Materials	Aluminium			
TECHNICAL SPECIFICATIONS				
Weight	31.2 kg / sqm			
Brightness	800 nits		800 - 1000 nits	1000 - 1200 nits
Contrast Ratio	6,500:1			
Viewing Angle	160°V - 160°H			
Gray level	14 - 16 bits			
Refresh Rate	3.840 Hz			
Power Input	AC100~AC240 50/60 Hz			
Maximun Power comsuption	800 W/m2			
Medium Power comsuption	200 W/m2			
Life hours	> 100,000			
IP grade	IP43			
Operating Temperature	from -20°C~60°C			
Storage Humidity	10% - 90% RH			
Maintenance access	Front			
ECOACTIVE FEATURES				
Nox & Sox Abatement	50.03%			
Certification of pollution abetment	CEN/TS 16980-1 / ISO 22197-1			
Antidust	Yes			
Self-cleaning	Yes			
Anti-bacterial	Yes			