



# IN All In One GOB

Datasheet



	P1.25 / 108"	P1.56 / 135"	P1.87 / 162"
<b>MODULE PARAMETERS</b>			
Pixel pitch	1.25 mm	1.56 mm	1.87 mm
Diagonal (inches)	108"	135"	162"
Module size	300mm x 168,75mm		
LED type	SMD1010		SMD1515
<b>CABINET SPECIFICATIONS</b>			
Cabinet size	600mm x 337,5mm x 22,5mm		
Cabinet Configuration	4 x 4	5 x 5	6 x 6
<b>SCREEN SPECIFICATIONS</b>			
Screen Size (W x H) mm	2400 x 1350	3000 x 1687,5	3600 x 2025
Screen resolution	1920 x 1080		
<b>TECHNICAL SPECIFICATIONS</b>			
Screen Weight (Wall / Hanging)	103 kg	149 kg	198 kg
Screen Weight (Trolley)	134 kg	183 kg	232 kg
Surface finish	GOB		
Brightness	1.000 nits		
Contrast Ratio	8,000:1		
Viewing Angle	160°V - 160°H		
Gray level	16 bits		
Refresh Rate	3.840 Hz		
Power Input	AC220 ~AC240		
Maximun Power comsuption	600 W/m2		
Average Power comsuption	200 W/m2		
Life hours	> 100,000		
IP grade	IP65 Front		
Shock Proof	IK 7		
Operating Temperature	from -10°C~40°C		
Storage Humidity	10% - 80% RH		
Maintenance access	Front		
Speackers	Stereo 2x 20w		
Input/Output	Audio in (S/PDIF) / HDMI IN 2.0 / HDMI OUT 2.0 / 3 USB port / RJ45 (Ethernet) / Mic-in / USB Type-c		
<b>ECOACTIVE FEATURES</b>			
Nox & Sox Abatement	50.03%		
Certification of pollution abetment	CEN/TS 16980-1 / ISO 22197-1		
Antidust	Yes		
Self-cleaning	Yes		
Anti-bacterial	Yes		