IN The Best

Datasheet



	P0.46	P0.62	P0.78	P0.93	P1.25	P1.56
MODULE PARAMETERS						
Pixel pitch	0.46 mm	0.62 mm	0.78 mm	0.93 mm	1.25 mm	1.56 mm
Module size	150 x 168.75 mm					
LED type	Flip Chip COB					
Module resolution	320 x 360	240 x 270	192 x 216	160 x 180	120 x 135	96 x 108
CABINET SPECIFICATIONS						
Cabinet size	600 x 337.5 x 44.5 mm					
Cabinet resolution	1280 x 720	960 x 540	768 x 432	640 x 360	480 x 270	384 x 216
Cabinet Materials	Die casting Aluminium					
TECHNICAL SPECIFICATIONS						
Weight per cabinet	30 kg / sqm					
Surface finish	Matte					
Brightness	600 - 1.200 nits					
Contrast Ratio	22,000:1					
Viewing Angle	179°V - 179°H					
Gray level	16 bits					
Refresh Rate	3.840 Hz /7.680 Hz					
Power Input	AC110 ~AC220					
Maximun Power comsuption	480 W/m2					
Medium Power comsuption	160 W/m2					
Life hours	> 100,000					
IP grade	IP65 Front / IP43 back					
Shock Proof	IK 7					
Operating Temperature	from -20°C~60°C					
Storage Humidity	10% - 90% RH					
Maintenance access	Front					
ECOACTIVE FEATURES						
Nox & Sox Abatement	50.03%					
Certification of pollution abetment	CEN/TS 16980-1 / ISO 22197-1					
Antidust	Yes					
Self-cleaning	Yes					
Anti-bacterial	Yes					